


N2XS(F)2Y 6/10 kV, 12/20 kV, 18/30 kV

XLPE-insulated, Cu-conductor, single core, longitudinally watertight, screened, PE-sheath



Technical data

- XLPE-insulated power cables acc. to DIN VDE 0276 part 620, HD 620 S2 and IEC 60502
- **Temperature range**
during installation up to -20°C
- **Operating temperature**
max. +90°C
- **Short circuit temperature**
+250°C (short circuit duration max. 5 s)
- **Nominal voltage**
U₀/U 6/10 kV, 12/20 kV, 18/30 kV
- **Operating voltage**, 50 Hz
for 6/10 kV = max. 12 kV
for 12/20 kV = max. 24 kV
for 18/30 kV = max. 36 kV
- **Test voltage**
for 6/10 kV = 21 kV
for 12/20 kV = 42 kV
for 18/30 kV = 63 kV
- **Minimum bending radius**
15x cable Ø
- **Power rating**
see "Technical Informations"

Cable structure

- Bare copper conductor, to DIN VDE 0295 cl.2, multi-wire, BS 6360 cl.2, IEC 60228 cl.2
- Inner semi-conducting coating
- Core insulation of cross-linked polyethylene (XLPE), compound type DIX8 to HD 620 S2
- Outer conductive layer extruded and permanently welded with the core insulation
- Longitudinally watertight, conductive wrapping
- Screen: Braiding of copper wires with one or two tapes applied helically
- Longitudinally water-tight wrapping
- Outer sheath of PE compound type DMP2 to HD 620 S2
- Sheath colour: black

Properties

- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers
- **Installation notes**
To guarantee an optimum on operating reliability the extruded semi-conductive layer is spliced with the insulation for long duration. For this reason we recommend a peeling tool for installation

Note

- rm = round conductor, multi-wire
- Further types and dimensions on request.
- AWG sizes are approximate equivalent values. The actual cross section is in mm².

Application

Suitable for indoor installation and in cable ducts, outdoors, underground and in water as well as for installation on cable trays for industries, switch-boards and power stations. The PE-outer sheath is resistant to high mechanical stress for laying the cables. This PE sheath is not flame retardant acc. to DIN EN 60332-1-2. The inner conducting layer between the conductor and the XLPE insulation and the firmly bonded outer conducting layer on the XLPE insulation assures a construction free of partial discharges with high operational reliability.

Part no.	No. cores x cross-sec. mm ²	Operation voltage max.	Nominal voltage kV	Insulation thickness mm	Screen cross-sec. mm ²	Sheath thickness Nominal value mm	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
32560	1 x 35 rm / 16	12	6 / 10	3,4	16	2,5	26,0	518,0	1050,0	2
32561	1 x 50 rm / 16	12	6 / 10	3,4	16	2,5	28,0	662,0	1150,0	1
32562	1 x 70 rm / 16	12	6 / 10	3,4	16	2,5	30,0	854,0	1460,0	2/0
32563	1 x 95 rm / 16	12	6 / 10	3,4	16	2,5	31,0	1094,0	1700,0	3/0
32564	1 x 120 rm / 16	12	6 / 10	3,4	16	2,5	32,0	1334,0	2030,0	4/0
32565	1 x 150 rm / 25	12	6 / 10	3,4	25	2,5	34,0	1723,0	2350,0	300 kcmil
32566	1 x 185 rm / 25	12	6 / 10	3,4	25	2,5	36,0	2059,0	2700,0	350 kcmil
32567	1 x 240 rm / 25	12	6 / 10	3,4	25	2,5	38,0	2587,0	3300,0	500 kcmil
32568	1 x 300 rm / 25	12	6 / 10	3,4	25	2,5	40,0	3163,0	3900,0	600 kcmil
32569	1 x 400 rm / 35	12	6 / 10	3,4	35	2,5	44,0	4234,0	4850,0	750 kcmil
32570	1 x 500 rm / 35	12	6 / 10	3,4	35	2,5	47,0	5194,0	6000,0	1000 kcmil
79954	1 x 630 rm / 35	12	6 / 10	3,4	35	2,5	49,0	6442,0	7020,0	1250 kcmil
32571	1 x 35 rm / 16	24	12 / 20	5,5	16	2,5	31,0	518,0	1210,0	2
32572	1 x 50 rm / 16	24	12 / 20	5,5	16	2,5	33,0	662,0	1400,0	1
32573	1 x 70 rm / 16	24	12 / 20	5,5	16	2,5	34,0	854,0	1550,0	2/0
32574	1 x 95 rm / 16	24	12 / 20	5,5	16	2,5	36,0	1094,0	1800,0	3/0
32575	1 x 120 rm / 16	24	12 / 20	5,5	16	2,5	37,0	1334,0	2150,0	4/0
32576	1 x 150 rm / 25	24	12 / 20	5,5	25	2,5	39,0	1723,0	2400,0	300 kcmil
32577	1 x 185 rm / 25	24	12 / 20	5,5	25	2,5	41,0	2059,0	2850,0	350 kcmil
32578	1 x 240 rm / 25	24	12 / 20	5,5	25	2,5	43,0	2587,0	3250,0	500 kcmil
32579	1 x 300 rm / 25	24	12 / 20	5,5	25	2,5	45,0	3163,0	3850,0	600 kcmil
32580	1 x 400 rm / 35	24	12 / 20	5,5	35	2,5	48,0	4234,0	4900,0	750 kcmil
32581	1 x 500 rm / 35	24	12 / 20	5,5	35	2,5	52,0	5194,0	6100,0	1000 kcmil
33092	1 x 630 rm / 35	24	12 / 20	5,5	35	2,5	54,0	6442,0	7340,0	1250 kcmil

Continuation ►

N2XS(F)2Y 6/ 10 kV, 12/20 kV, 18/30 kV

XLPE-insulated, Cu-conductor, single core, longitudinally watertight, screened, PE-sheath



Part no.	No. cores x cross-sec. mm ²	Operation voltage max.	Nominal voltage kV	Insulation thickness mm	Screen cross-sec. mm ²	Sheath thickness Nominal value mm	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
32582	1 x 50 mm / 16	36	18 / 30	8	16	2,5	37,0	662,0	1700,0	1
32583	1 x 70 mm / 16	36	18 / 30	8	16	2,5	38,0	854,0	1950,0	2/0
32584	1 x 95 mm / 16	36	18 / 30	8	16	2,5	40,0	1094,0	2300,0	3/0
32585	1 x 120 mm / 16	36	18 / 30	8	16	2,5	42,0	1334,0	2600,0	4/0
32586	1 x 150 mm / 25	36	18 / 30	8	25	2,5	43,0	1723,0	3000,0	300 kcmil
32587	1 x 185 mm / 25	36	18 / 30	8	25	2,5	45,0	2059,0	3350,0	350 kcmil
32588	1 x 240 mm / 25	36	18 / 30	8	25	2,5	47,0	2587,0	4100,0	500 kcmil
32589	1 x 300 mm / 25	36	18 / 30	8	25	2,5	50,0	3163,0	4800,0	600 kcmil
32590	1 x 400 mm / 35	36	18 / 30	8	35	2,5	53,0	4234,0	5750,0	750 kcmil
32591	1 x 500 mm / 35	36	18 / 30	8	35	2,5	56,0	5194,0	6700,0	1000 kcmil
708487	1 x 630 mm / 35	36	18 / 30	8	35	2,5	59,0	6442,0	7760,0	1250 kcmil

Dimensions and specifications may be changed without prior notice. (RQ03)