



EF

Universal applications.
Protection tube from reinforced, galvanised steel band with spiral wound, latched profile, a continuous cord seal and extruded plastic sheath.

This complex construction method keeps the plastic sheath and the internal tube flush together.

Material

Galvanised steel
Outer sheath material: PVC

Technical Data

Temperature range: -25°C to +70°C
Temperature range temporary up to +90°C

Note

Suitable connection glands:
T&B straight, T&B angled, Anamet straight, Anamet angled.
Dimensions 2 1/2", 3", 4", 5" and 6" available on request.

Part No. grey	Part No. black	Trade size PG	Inner Ø mm	Outer Ø mm	Bending radius mm	Per metres	net EUR/100 metres at acceptance of		
							up to 100	101 - 500	501 - 1000
91229	96939	7	6,4	11,5	-	50	o. r.	o. r.	o. r.
91230	96248	9	10,1	14,4	-	50	o. r.	o. r.	o. r.
91231	96249	11	12,6	17,8	-	75	o. r.	o. r.	o. r.
91232	97153	16	16,0	21,1	-	60	o. r.	o. r.	o. r.
91233	96718	21	21,0	26,4	-	50	o. r.	o. r.	o. r.
91234	96250	29	26,5	33,1	-	30	o. r.	o. r.	o. r.
91235	96251	36	35,1	41,8	-	30	o. r.	o. r.	o. r.
91236	97175	42	40,3	47,8	-	15	o. r.	o. r.	o. r.
91237	96252	48	51,6	59,9	-	15	o. r.	o. r.	o. r.

small pack

Part No. grey	Part No. black	Trade size PG	Inner Ø mm	Outer Ø mm	Bending radius mm	Per metres	net EUR/100 metres at acceptance of		
							up to 100	101 - 500	501 - 1000
94915	94930	9	10,1	14,4	-	10	o. r.	o. r.	o. r.
94916	94931	11	12,6	17,8	-	10	o. r.	o. r.	o. r.
94917	94932	16	16,0	21,1	-	10	o. r.	o. r.	o. r.
94918	94933	21	21,0	26,4	-	10	o. r.	o. r.	o. r.

o. r. = on request