



## Braided sleeve

The screened and interference suppression braided sleeve for directionality and for the mechanical protection of electrical cables and lines.

## Properties

Axially compressible

## Application

Plant and machine construction Robot construction Automation technology Vehicle construction and shipbuilding Rail technology Installation technology Control cabinet construction

## Material

Copper, galvanised resp. Galvanised steel

## Technical data

Copper, galvanised:  
Temperature range: -75°C to +150°C

Galvanised steel:  
Temperature range: -75°C to +300°C

## copper

Part No.	Min. inner Ø mm	Max. inner Ø mm	Per metres	net EUR/100 metres at acceptance of		
				up to 100	101 - 500	501 - 1000
97397	5,0	12,0	100,0	o. r.	o. r.	o. r.
97399	8,0	17,0	50,0	o. r.	o. r.	o. r.
97400	12,0	22,0	50,0	o. r.	o. r.	o. r.
97402	16,0	27,0	50,0	o. r.	o. r.	o. r.
97403	20,0	35,0	25,0	o. r.	o. r.	o. r.

## steel

Part No.	Min. inner Ø mm	Max. inner Ø mm	Per metres	net EUR/100 metres at acceptance of		
				up to 100	101 - 500	501 - 1000
97197	5,0	12,0	100,0	o. r.	o. r.	o. r.
97199	8,0	17,0	50,0	o. r.	o. r.	o. r.
97200	12,0	22,0	50,0	o. r.	o. r.	o. r.
97202	16,0	27,0	50,0	o. r.	o. r.	o. r.
96561	20,0	35,0	25,0	o. r.	o. r.	o. r.

o. r. = on request