

HTP (High Temperature Protection)



HTP

This product is extremely heat resistant. HTP has a high insulation factor and, due to the iron oxide containing silicone sheath, is resistant to small quantities of liquid steel. HTP also protects against burn injuries from steam tubes, hot air or hot water lines.

Material

Interior sheath of knitted glass-fibre braid

Silicone sheath (contains iron oxide)

Colour: orange

Technical data

Permanent load: +260°C

Short-time load: +1090°C

(up to approx. 20 minutes)

Loading moment: +1640°C

(approx. 15-30 seconds)

tube

Part No. Tube version	Inner Ø mm	Width mm	Per metres	net EUR/100 metres at acceptance of		
				up to 100	101 - 500	501 - 1000
93630	6,0	-	15,0	o. r.	o. r.	o. r.
93631	8,0	-	15,0	o. r.	o. r.	o. r.
93632	10,0	-	15,0	o. r.	o. r.	o. r.
93633	14,0	-	15,0	o. r.	o. r.	o. r.
93634	19,0	-	15,0	o. r.	o. r.	o. r.
93635	22,0	-	15,0	o. r.	o. r.	o. r.
93636	25,0	-	15,0	o. r.	o. r.	o. r.
93637	32,0	-	15,0	o. r.	o. r.	o. r.
93638	38,0	-	15,0	o. r.	o. r.	o. r.
93639	44,0	-	15,0	o. r.	o. r.	o. r.
93640	54,0	-	15,0	o. r.	o. r.	o. r.
93641	64,0	-	15,0	o. r.	o. r.	o. r.
93642	76,0	-	15,0	o. r.	o. r.	o. r.
93643	89,0	-	15,0	o. r.	o. r.	o. r.
93644	102,0	-	15,0	o. r.	o. r.	o. r.

wrapping tape

Part No. Cable wrap version	Inner Ø mm	Width mm	Per metres	net EUR/100 metres at acceptance of		
				up to 100	101 - 500	501 - 1000
94721	-	25,0	15,0	o. r.	o. r.	o. r.
94722	-	51,0	15,0	o. r.	o. r.	o. r.
94723	-	76,0	15,0	o. r.	o. r.	o. r.
94724	-	102,0	15,0	o. r.	o. r.	o. r.
94758	-	127,0	15,0	o. r.	o. r.	o. r.
94759	-	152,0	15,0	o. r.	o. r.	o. r.

adhesive tape

Part No. Adhesive tape version	Inner Ø mm	Width mm	Per metres	net EUR/100 metres at acceptance of		
				up to 100	101 - 500	501 - 1000
93645	-	25,0	11,0	o. r.	o. r.	o. r.

o. r. = on request