

IREV-S (indoor terminations for shrinking)



IREV-S

The interior end seals are suitable for all single-conductor and three-conductor medium-range voltage plastic cables with differing conductor layers and sheath designs up to 18/30(36)kV.

Scope of delivery

- Unit: 1
- aufschiebbares Silikon-Feldsteuerelement
- sealing band
- creeping current resistant, weather-proof heat shrink-on tube
- assembly instruction

Properties

- Safe field effect
- Simple assembly
- Wider application range
- Excellent external layer behaviour
- Unlimited conductivity
- Immediately operational

Notes

An additional earthing kit is required for cables with copper sheath.

Single core

Part No.	Type	Nominal voltage U ₀ /U(U _m)	Cross section mm ²	Units	net EUR/items at acceptance of		
					1	2 - 5	6 - 10
93190	IREV-S12/1	6/10kV	10,0 - 25,0	1	o. r.	o. r.	o. r.
93191	IREV-S12/1	6/10kV	25,0 - 95,0	1	o. r.	o. r.	o. r.
94420	IREV-S12/1	6/10kV	95,0 - 240,0	1	o. r.	o. r.	o. r.
93192	IREV-S12/1	6/10kV	150,0 - 400,0	1	o. r.	o. r.	o. r.
93193	IREV-S12/1	6/10kV	240,0 - 500,0	1	o. r.	o. r.	o. r.
94421	IREV-S12/1	6/10kV	400,0 - 800,0	1	o. r.	o. r.	o. r.
94422	IREV-S12/1	6/10kV	800,0 - 1000,0	1	o. r.	o. r.	o. r.
94423	IREV-S24/1	12/20kV	10,0 - 35,0	1	o. r.	o. r.	o. r.
93194	IREV-S24/1	12/20kV	25,0 - 95,0	1	o. r.	o. r.	o. r.
93195	IREV-S24/1	12/20kV	95,0 - 185,0	1	o. r.	o. r.	o. r.
93196	IREV-S24/1	12/20kV	120,0 - 300,0	1	o. r.	o. r.	o. r.
93197	IREV-S24/1	12/20kV	240,0 - 500,0	1	o. r.	o. r.	o. r.
94424	IREV-S24/1	12/20kV	630,0 - 1000,0	1	o. r.	o. r.	o. r.
93198	IREV-S36/1	18/30kV	35,0 - 70,0	1	o. r.	o. r.	o. r.
94425	IREV-S36/1	18/30kV	50,0 - 150,0	1	o. r.	o. r.	o. r.
93199	IREV-S36/1	18/30kV	150,0 - 400,0	1	o. r.	o. r.	o. r.
93200	IREV-S36/1	18/30kV	500,0 - 800,0	1	o. r.	o. r.	o. r.

Triple core

Part No.	Type	Nominal voltage U ₀ /U(U _m)	Cross section mm ²	Units	net EUR/items at acceptance of		
					1	2 - 5	6 - 10
94435	IREV-S12/3	6/10kV	10,0 - 25,0	1	o. r.	o. r.	o. r.
93201	IREV-S12/3	6/10kV	25,0 - 95,0	1	o. r.	o. r.	o. r.
93202	IREV-S12/3	6/10kV	95,0 - 240,0	1	o. r.	o. r.	o. r.
93203	IREV-S12/3	6/10kV	150,0 - 400,0	1	o. r.	o. r.	o. r.
94436	IREV-S24/3	12/20kV	10,0 - 35,0	1	o. r.	o. r.	o. r.
94437	IREV-S24/3	12/20kV	25,0 - 95,0	1	o. r.	o. r.	o. r.
94438	IREV-S24/3	12/20kV	70,0 - 240,0	1	o. r.	o. r.	o. r.
94439	IREV-S24/3	12/20kV	120,0 - 300,0	1	o. r.	o. r.	o. r.

o. r. = on request