

# MSVM-S (low voltage sleeve for shrinking)



## MSVM-S

The centre tension transition sleeve suitable for connecting all single-core plastic power cables with external conductor layer to up to 18/30(36)kV.

For connecting cables with differing cross-sections, conductor materials and cable designs with regard to external conductor layer and sheathing.

## Scope of delivery

- Unit: 1
- Field effect filler tape (blue)
- thick-walled heat shrink-on tube
- cooper fabric shielding
- heat shrink-on tube as an outside protection
- assembly instruction

## Properties

- Safe field effect
- Simple assembly
- Large cross-sections
- Unlimited conductivity
- Immediately operational

Part No.	Type	Nominal voltage U <sub>0</sub> /U(Um)	Cross section mm <sup>2</sup>	Diameter from - to mm	Units	net EUR/items at acceptance of		
						1	2 - 5	6 - 10
93107	MSVM-S12/1	6/10kV	35,0 - 95,0	13,2 - 20,0	1	o. r.	o. r.	o. r.
93108	MSVM-S12/1	6/10kV	95,0 - 240,0	18,2 - 25,0	1	o. r.	o. r.	o. r.
93109	MSVM-S12/1	6/10kV	150,0 - 300,0	20,9 - 35,0	1	o. r.	o. r.	o. r.
93110	MSVM-S12/1	6/10kV	300,0 - 400,00	28,6 - 45,0	1	o. r.	o. r.	o. r.
93111	MSVM-S12/1	6/10kV	500,0 - 800,0	28,6 - 60,0	1	o. r.	o. r.	o. r.
93117	MSVM-S24/1	12/20kV	10,0 - 35,0	13,2 - 15,0	1	o. r.	o. r.	o. r.
93118	MSVM-S24/1	12/20kV	50,0 - 150,0	18,2 - 25,0	1	o. r.	o. r.	o. r.
93119	MSVM-S24/1	12/20kV	70,0 - 240,0	20,9 - 30,0	1	o. r.	o. r.	o. r.
93120	MSVM-S24/1	12/20kV	150,0 - 300,0	24,2 - 35,0	1	o. r.	o. r.	o. r.
93379	MSVM-S24/1	12/20kV	400,0 - 650,0	28,6 - 45,0	1	o. r.	o. r.	o. r.
93398	MSVM-S24/1	12/20kV	630,0 - 1000,0	28,6 - 45,0	1	o. r.	o. r.	o. r.
93121	MSVM-S36/1	18/30kV	35,0 - 50,0	20,9 - 18,0	1	o. r.	o. r.	o. r.
93122	MSVM-S36/1	18/30kV	70,0 - 150,0	24,2 - 25,0	1	o. r.	o. r.	o. r.
93123	MSVM-S36/1	18/30kV	150,0 - 300,0	28,6 - 35,0	1	o. r.	o. r.	o. r.
93124	MSVM-S36/1	18/30kV	300,0 - 500,0	28,6 - 45,0	1	o. r.	o. r.	o. r.

o. r. = on request