

PV H4 male coupling connector

NEW



Technical Data

- Protection classification: IP 68
- Temperature range: -40°C up to +90°C (IEC)
- Rated voltage: 1000 A (IEC)
- Rated current: 45 A (4 mm²), 52 A (6 mm²)
- Contact resistance: 0.25 mΩ
- Contact material: Copper, tinned, cross-linked
- Insulation material: PBT
- Contact type: cross-linked

RoHS

Part No.	Designation	Core cross section mm ²	Cable Ø mm	Unit Pcs.
905593	PV-100508-M	4	4,5 - 7,8	100
905595	PV-100506-M	6	4,5 - 7,8	100
905937	PV-100510-M	10	4.5 - 7.8	100

PV H4 female coupling connector

NEW



Technical Data

- Protection classification: IP 68
- Temperature range: -40°C up to +90°C (IEC)
- Rated voltage: 1000 A (IEC)
- Rated current: 45 A (4 mm²), 52 A (6 mm²)
- Contact resistance: 0.25 mΩ
- Contact material: Copper, tinned, cross-linked
- Insulation material: PBT
- Contact type: cross-linked

RoHS

Part No.	Designation	Core cross section mm ²	Cable Ø mm	Unit Pcs.
905594	PV-100508-F	4	4,5 - 7,8	100
905596	PV-080506-F	6	4,5 - 7,8	100
905938	PV-100510-F	10	4.5 - 7.8	100