

Terminals ADI-B (insulated)



ADI-B

Tape products for processing with Stripax-Plus (strip products) or automatic crimpers (coil products). Insulated core end sleeves prevent stripped wires from fanning. The hopper-shaped plastic collar enables them to be pushed easily onto the wires.

Material

- halogen-free

Socket: copper
Surface: tinned

Insulating shroud: polypropylene

Note

Delivery formats:
Strips: 1 item = 10 strips x 50 pcs.
Coils: Endless on cardboard coil

Technical data

Temperature range up to: +105°C
Temperature range temporary: +120°C

strips

Part No.	Size mm ²	Colour	Total length mm	Stick length mm	Units	net EUR/100 items at acceptance of		
						up to 5000	5001 - 10000	10001 - 50000
91912	0,5	white	14,0	8,0	500	o. r.	o. r.	o. r.
91913	0,5	orange	14,0	8,0	500	o. r.	o. r.	o. r.
91914	0,75	grey	14,0	8,0	500	o. r.	o. r.	o. r.
91915	0,75	white	14,0	8,0	500	o. r.	o. r.	o. r.
91916	0,75	light blue	14,0	8,0	500	o. r.	o. r.	o. r.
91917	1,0	red	14,0	8,0	500	o. r.	o. r.	o. r.
91918	1,0	yellow	14,0	8,0	500	o. r.	o. r.	o. r.
91919	1,5	black	14,0	8,0	500	o. r.	o. r.	o. r.
91920	1,5	red	14,0	8,0	500	o. r.	o. r.	o. r.
91921	2,5	blue	14,0	8,0	500	o. r.	o. r.	o. r.
91922	2,5	grey	14,0	8,0	500	o. r.	o. r.	o. r.

spools

Part No.	Size mm ²	Size	Total length mm	Stick length mm	Units	net EUR/100 items at acceptance of		
						up to 5000	5001 - 10000	10001 - 50000
93036	0,5	white	14,0	8,0	10000	o. r.	o. r.	o. r.
93037	0,5	orange	14,0	8,0	10000	o. r.	o. r.	o. r.
93038	0,75	light blue	14,0	8,0	10000	o. r.	o. r.	o. r.
93039	0,75	white	14,0	8,0	10000	o. r.	o. r.	o. r.
93040	0,75	grey	14,0	8,0	10000	o. r.	o. r.	o. r.
93041	1,0	red	14,0	8,0	7500	o. r.	o. r.	o. r.
93042	1,0	yellow	14,0	8,0	7500	o. r.	o. r.	o. r.
93043	1,5	black	14,0	8,0	7500	o. r.	o. r.	o. r.
93046	1,5	red	14,0	8,0	7500	o. r.	o. r.	o. r.
93047	2,5	grey	14,0	8,0	5000	o. r.	o. r.	o. r.
93048	2,5	blue	14,0	8,0	5000	o. r.	o. r.	o. r.

o. r. = on request



HELUKABEL®

Cable accessories