


Audio

Audio cables with braided shielding

HELUSOUND[®]



Type

Cable structure

Conductor material:
Core insulation:
Core colours:
Stranding element:
Sheath material:
Cable external diameter:
Sheath colour:

HELUSOUND audio cable analog

2x0,25 + 0,25

Copper, bare
PVC
rd, wh
2 cores with 1 filler and 1 earth conductor stranded
PVC
approx. 3,4 mm
black

Electrical data

Conductor resistance, max.: 75 Ohm/km
Insulation resistance, min.: 5 MOhm x km

Technical data

Weight: approx. 20 kg/km
Min. bending radius for laying: 35 mm
Operating temperature range min.: -25°C
Operating temperature range max.: +70°C
Copper weight: 13,5 kg/km

Part no.	Cable structure	Conductor resistance Ohm / km	Outer diameter approx. mm	Cop. weight kg / km	Weight approx. kg / km
400000	2x0,25 + 0,25	< 75,0	3,4	13,5	20,0
400001	2x0,33+0,33	< 60,0	4,0	16,3	26,0
400002	2x0,5+0,33	< 36,8	5,6	26,1	49,0

Dimensions and specifications may be changed without prior notice.

Application

The HELUSOUND[®] audio cable is a 2-core, shielded multipurpose cable with earth conductor. It is particularly suitable for use in microphone, radio, studio and transmission systems.

Analog cable for short transmission distances and low frequencies.